

TECHNICAL DATA

Size Range:	DN40 - DN600 (1 1/2" - 24")
Flange Drilling:	AS2129 Table E (standard) AS4087 CL16, AS4087 CL35 (optional)
Pressure Rating:	PN16, PN25
Features:	<ul style="list-style-type: none"> Fusion bonded epoxy coated. Stainless steel screen & fasteners. Drain or flush plug in lid. Low pressure drop.

MATERIAL SPECIFICATIONS & PARTS LIST

NO.	DESCRIPTION	MATERIAL
1	Body	Cast Iron
2	Gasket	Graphite Steel
3	Plug	SS304
4	Bonnet	Cast Iron
5	Screen	SS304 (woven wire mesh tyoe)

DIMENSIONS (MM)

AS105F DN40 - DN600											
DN	NPS	FxF	b	ØD	ØD1	n-Ød1	h1	ØS	S1xS2	W	Weight (Kg)
40	1 1/2"	200	14.2	135	98	4-14	135	46	1.2x1.2	93	6.5
50	2"	225.4	15.8	150	114	4-18	150	54	1.2x1.2	110	9.6
65	2 1/2"	273	17.5	165	127	4-18	160	70	1.2x1.2	135	12.3
80	3"	292	19	185	146	4-18	200	86	1.2x1.2	155	17
100	4"	352.4	23.9	215	178	8-18	240	110	1.2x1.2	205	28.1
125	5"	416	23.9	255	210	8-18	290	135	1.2x1.2	225	40
150	6"	470	25.4	280	235	8-22	330	164	1.5x1.7	260	48.9
200	8"	543	28.5	335	292	8-22	380	210	1.5x1.7	318	82.3
250	10"	660.4	30.2	405	356	12-22	480	258	1.5x1.7	400	127.3
300	12"	762	31.8	455	406	12-26	550	308	1.5x1.7	454	200
350	14"	946.3	35	525	470	12-26	680	358	1.5x1.7	560	320
400	16"	1079	36.6	580	521	12-26	780	408	1.5x1.7	600	420
450	18"	1168	39.6	640	584	16-26	910	469	1.1x1.1	832	620
500	20"	1275	42.9	705	641	16-26	968	520	1.1x1.1	851	780
600	24"	1450	47.8	825	756	16-33	1160	623	1.1x1.1	1066	1050

FACTORY ACCREDITED:



FIRE SAFETY
APPROVAL AP1607

6D-0645

No. WZ 1093
HH 1

NUMBER
0035

Designs, materials and specifications shown are subject to change without notice due to our continuing program of product development. AS105F_V1_20131111.

All content is protected by Copyright and is owned and/or licensed by AVFI Pty Ltd. Copyright © AVFI Pty Ltd.

