

ASL SERIES

PILOT OPERATED SOLENOID VALVES



The ASL range is a pilot operated solenoid valve that will work from 0.5 bar pressure and is available in brass or stainless steel. Models include ASLA which is normally closed (energise to open) or ASLAH normally open (energise to close).

All models feature investment cast body, interchangeable coils and PTFE diaphragm. The SLA range is specifically designed for steam or water pressures up to PN25.

ADVANTAGES

- ▷ Normally closed or normally open models.
- ▷ Brass or stainless steel body materials.
- ▷ PTFE diaphragm, others available on request.
- ▷ LED din plug available.
- ▷ All voltages interchangeable.



ASLA



ASLAH-316

TECHNICAL DATA

Size Range	10mm - 50mm (3/8" - 2")
Suitable for	Steam, water, air & oil under 20 CST
Maximum Temperature	185°C
Voltages	24VAC, 240VAC, 12VDC, 24VDC, 110VAC
Connections	BSPF (standard) NPT (optional)

ASL SERIES

PILOT OPERATED SOLENOID VALVES


MATERIAL SPECIFICATIONS & PARTS LIST

NO.	DESCRIPTION	MATERIAL
1	Valve Cover	Brass / 316SS
2	Diaphragm	Viton
3	Valve Body	Brass / 316SS


DIMENSIONS (MM)

MODEL	FUNCTION	BODY MATERIAL	DN	NPS	L x H (MM)	CV FACTOR	
ASLA & ASLA-316	Normally Closed	ASLA (Brass)	ASLA-316 (SS316)	10	3/8"	75x129	4.5
				15	1/2"	75x129	4.5
				20	3/4"	85x141	9
				25	1"	100x148	13
				32	1 1/4"	120x168	26
				40	1 1/2"	120x168	26
				50	2"	150x190	45
ASLAH & ASLAH-316	Normally Open	ASLAH (Brass)	ASLAH-316 (SS316)	10	3/8"	75x147	4.5
				15	1/2"	75x147	4.5
				20	3/4"	85x159	9
				25	1"	100x166	13
				32	1 1/4"	120x186	26
				40	1 1/2"	120x186	26
				50	2"	150x205	45

DIMENSIONAL DRAWING



PRESSURE LOSS



SELECTION LIST

MODEL & SIZE	MINIMUM PRESSURE	OPERATING PRESSURE BAR (AIR)		OPERATING PRESSURE BAR (WATER)		OPERATING PRESSURE BAR (OIL)		STEAM	POWER CONSUMPTION	COIL TYPE & CODE (D=DIN PLUG)						
		AC	DC	AC	DC	AC	DC			AC/DC	24/240VAC (VOLTS AMPS)	12/24DC (WATTS)	240VAC	24VAC	24VDC	12VDC
ASLA & ASLA-316																
10 - 50	0.5	25	20	25	20	20	20	10	48/20	28.5/20	D01-41014	D01-4104	D01-4106	D03-5107		
ASLAH & ASLAH-316																
10 - 25	0.5	8	8	8	8	8	8	8	48/20	28.5/20	D01-41014	D01-4104	D01-4106	D03-5107		
32 - 50	0.5	6	6	6	6	6	6	6	48/20	28.5/20	D01-41014	D01-4104	D01-4106	D03-5107		

ORDERING CHART

MODEL	STATE		MATERIAL		SIZE	COIL TYPE	
ASL	-A	Normal Closed	-	Brass	-10	12VDC	240VAC
	-AH	Normal Open	-316	316 Stainless Steel	-15	24VDC	110VAC
					-20	24VAC	

EXAMPLE	ASL, Normally Closed, Brass, 10mm, 12VDC
	ASL-A-10-12VDC

54 Enterprise Drive, Bundoora, VIC, 3083
 p. 1300 789 256 | e. sales@avfi.com.au
 avfi.com.au

Designs, material and specifications shown are subject to change without notice due to our continuing program of product development.

All content is protected by Copyright and is owned and/or licensed by AVFI Pty Ltd. Copyright © AVFI Pty Ltd

